



**1-1/4 in. Malleable Iron 90 Degree Elbow.
 Class 300 Rating, Threaded Connection,
 Galvanized**

<u>Item No.</u>	M116937	<u>UOM</u>	EA
-----------------	---------	------------	----


[View Product Online to Request Quote](#)

Specifications

Type	90 Degree Elbow
Item Remarks	Galvanized
Size	1-1/4 in.
Material	Iron
Material Grade	Malleable Iron
Pressure Class	Class 300
Connection	Threaded
Specification	ASME B16.3
Market	Commercial


Product URL: <https://torksystems.com/M116937>

Malleable Iron Threaded Fittings - Class 150



90° Elbow

Size in	A in	Packing		Weight lb
		Inner	Master	
1/8	0.69	50	800	0.1
1/4	0.81	35	560	0.1
3/8	0.95	45	360	0.2
1/2	1.12	50	200	0.2
3/4	1.31	35	140	0.3
1	1.50	20	80	0.6
1-1/4	1.75	20	40	0.9
1-1/2	1.94	15	30	1.2
2	2.25	8	16	1.8
2-1/2	2.70	6	12	3.1
3	3.08	-	7	3.9
3-1/2	3.42	-	4	6.6
4	3.79	-	3	7.5
5	4.50	-	2	13.2
6	5.13	-	1	19.8
8	6.38	-	1	32.0



90° Reducing Elbow

Size in	A in	B in	Packing		Weight lb
			Inner	Master	
1/4 x 1/8	0.76	0.74	40	640	0.2
3/8 x 1/8	0.85	0.81	70	560	0.2
3/8 x 1/4	0.90	0.88	60	480	0.2
1/2 x 1/8	0.98	0.96	50	400	0.2
1/2 x 1/4	0.98	0.97	40	320	0.2
1/2 x 3/8	1.04	1.03	50	200	0.2
3/4 x 1/8	1.08	1.02	40	160	0.3
3/4 x 1/4	1.08	1.05	40	160	0.3
3/4 x 3/8	1.13	1.12	40	160	0.3
3/4 x 1/2	1.22	1.20	40	160	0.3
1 x 1/4	1.22	1.10	25	300	0.3
1 x 3/8	1.27	1.18	25	100	0.5
1 x 1/2	1.36	1.26	25	100	0.4
1 x 3/4	1.45	1.37	25	100	0.5
1-1/4 x 1/2	1.53	1.34	20	80	0.6
1-1/4 x 3/4	1.62	1.45	15	60	0.7
1-1/4 x 1	1.67	1.58	10	40	0.8
1-1/2 x 1/2	1.75	1.52	15	60	0.8
1-1/2 x 3/4	1.75	1.52	10	40	0.8
1-1/2 x 1	1.80	1.65	10	40	0.9
1-1/2 x 1-1/4	1.88	1.82	8	32	1.1
2 x 1/2	1.97	1.60	10	40	1.2
2 x 3/4	1.97	1.60	10	40	1.2
2 x 1	2.02	1.73	14	28	1.5
2 x 1-1/4	2.10	1.90	10	20	1.5
2 x 1-1/2	2.16	2.02	10	20	1.6
2-1/2 x 3/4	2.30	1.73	10	20	1.9
2-1/2 x 1	2.36	1.87	8	16	2.1
2-1/2 x 1-1/4	2.44	2.03	8	16	2.2
2-1/2 x 1-1/2	2.51	2.16	8	16	2.3
2-1/2 x 2	2.60	2.39	8	16	2.6
3 x 1/2	2.56	1.69	10	20	6.0
3 x 3/4	2.60	1.87	8	16	6.6
3 x 1	2.66	1.99	8	16	2.4
3 x 1-1/4	2.74	2.16	5	10	6.0
3 x 1-1/2	2.80	2.28	-	8	2.5
3 x 2	2.89	2.52	-	8	2.7
3 x 2-1/2	2.99	2.83	-	8	4.0
4 x 1-1/2	2.31	2.50	-	5	4.7
4 x 2	3.41	2.74	-	5	5.1
4 x 2-1/2	3.50	3.05	-	5	6.3
4 x 3	3.60	3.30	-	5	6.6