



4 in. Bronze Lift Check Valve. Class 150 Rating, Flanged Connection, Bronze Trim, Angle. OKV

<u>Item No.</u>	M101941	<u>UOM</u>	EA
<u>Brand</u>	OKV		

[View Product Online to Request Quote](#)

Specifications

Type	Lift Check Valve
Item Remarks	Angle
Size	4 in.
Material	Bronze, Brass, Al-Brz
Material Grade	Bronze
Trim	Bronze
Pressure Class	Class 150
Connection	Flanged
Specification	ANSI B16.24
Market	Commercial

Product URL: <https://torksystems.com/M101941>

Hydro Test Pressure		psi
Empty	246	350
Seat	158	225

Technical drawing of a mechanical device, likely a valve or actuator, showing a side view and a top view. The side view includes dimensions: ϕd , ϕC , ϕD , and H . The top view shows a circular flange with six mounting holes. Numbered callouts (1-12) identify various components.

12	Slide Plug	B124-C3700
11	Hinge Pin	
10	Cover Stud Bolt	
9	Cover Nut	
8	Disc Nut	B16-C3600
7	Cotter Pin	B124-C3700
6	Gasket	Non-Asbestos
4	Disc	B6C-CB3600
3	Hinge Arm	
2	Cover	
1	Body	
N.D.	COMPONENT	MATERIAL

△					
△					
△	First Issued				
No.		ALTERNATION			
TITLE	BRONZE, SWING CHECK VALVE				
	ASME 150Lbs				
DRAWN	CHECK.	APPROD.	DATE	SCALE	
JHKANG			TYPE	2011.03.31	1:1
			DWG. NO.	Revised Bennett	
				SVV-DC-1500-2-12B	

DIMENSION										Unit: mm	
SIZE	No	FLANGE ASME 150Lbs FF					L	H	ØD2	Remark	
		ØD	ØC	n-Øh	t						
2"	508	150	128.7	4-19.1	12.7	20.3	155	180			
2-1/2"	635	180	139.7	4-19.1	14.2	21.6	159	240			
3"	762	190	152.4	4-19.1	15.7	24.1	160	224			
4"	101.6	230	150.5	8-19.1	17.5	29.2	180	280			
5"	127	255	215.9	8-22.4	19.1	35.6	210	315			
6"	152.4	280	241.3	8-22.4	20.6	40.5	210	355			
8"	203.2	345	298.5	8-22.4	22.9	45.5	260	355			
10"	254	405	362	12-25.4	25.4	62.2	310	355			
12"	304.8	405	431.8	12-25.4	28.9	69.9	320	400			